



### Carbon Filled Breathers - Fume/Odor Removal

Model	Height inches (cm)	Diameter inches (cm)	Both Ends Connection	Mounting Connection	Silica Gel lbs (kg)	Carbon Weight lbs (kg)	Maximum Adsorption Capacity fl. ounces (mL)	Maximum Air Flow cfm	Maximum Reservoir Fluid Flow gpm	Type of Medium	Replacement Activated Carbon Bag No.	Weight of Activated Carbon Bag lbs (kg)	Replacement Polyester Pleated Filter No.	Filter Weight lbs (kg)	Uses Replacement Cartridge
D-200	3.5(8.9)	5 (12.7)		1" slip fit		0.5 (0.2)		20	150	100% Activated Carbon					
D-201	5 (12.7)	5 (12.7)		1" slip fit		0.8 (0.4)		20	150	100% Activated Carbon					
D-202	8 (20.3)	5 (12.7)		1" slip fit		1.6 (0.7)		20	150	100% Activated Carbon					
D-208	10 (25.4)	5 (12.7)		2" MNPT		2.1 (1.0)		20	150	100% Activated Carbon					
G-2	10 (25.4)	5 (12.7)		2" FNPT	1.5 (0.7)	1.2 (0.5)	9.20 (272)	20	150	50% Activated Carbon 50% Silica Gel					
L-241	5.5 (14.0)	2 (5.1)	½" FNPT			0.1 (.05)		6	45	100% Activated Carbon					
L-242	8.5 (21.6)	2 (5.1)	½" FNPT			0.2 (0.1)		6	45	100% Activated Carbon					
L-243	5.5 (14.0)	3.24 (8.2)	½" FNPT			0.4 (0.2)		6	45	100% Activated Carbon					

L-244	8.5 (21.6)	3.24 (8.2)	½" FNPT			0.8 (0.4)		6	45	100% Activated Carbon					
L-344	8.5 (21.6)	3.25 (8.3)	½" FNPT			0.9 (0.4)	n/a	4.91 (145)	6	45	33% Activated Carbon 67% Silica Gel				
M-203	6.6 (16.8)	10 (25.4)		1" MNPT		1.0 (0.5)			15	112	100% Activated Carbon	095A207	1 (0.5)	A95A204	2.0 (0.9)
M-204	6.6 (16.8)	10 (25.4)		2" MNPT		1.0 (0.5)			15	112	100% Activated Carbon	095A207	1 (0.5)	A95A204	2.0 (0.9)
M-205	12 (30.5)	10 (25.4)		1" MNPT		2.5 (1.1)			15	112	100% Activated Carbon	095A208	2.5 (1.1)	095A205	3.0 (1.4)
M-206	12 (30.5)	10 (25.4)		2" MNPT		2.5 (1.1)			50	375	100% Activated Carbon	095A208	2.5 (1.1)	095A205	3.0 (1.4)
M-207	13.5 (34.3)	16 (40.6)		3" MNPT		11.0 (5)			125	938	100% Activated Carbon	095A209	11 (5)	A95A206	5.0 (2.3)
R-200	5 (12.7)	5.2 (13.2)		1" MNPT	0.5 (0.2)				25	187	100% Activated Carbon				A-303
R-201	6.5 (16.5)	5.2 (13.2)		1" MNPT		0.8 (0.4)			25	187	100% Activated Carbon				A-304
R-202	9.5 (24.1)	5.2 (13.2)		1" MNPT		1.6 (0.7)			25	187	100% Activated Carbon				A-305
R-223	12 (30.5)	5.2 (13.2)		2" MNPT		2.1 (1.0)			25	187	100% Activated Carbon				A-324

R-325	12 (30.5)	5.2 (13.2)		2" MNPT	2.2 (1.0)	0.7 (0.3)	13.46 (398)	25	187	33% Activated Carbon 67% Silica Gel					A-325
Z-231	2 (5.1)	2 (5.1)		½" FNPT		0.05 (0.2)		5	37	100% Activated Carbon					
Z-232	3.25 (8.3)	2 (5.1)		½" FNPT		0.09 (.04)		5	37	100% Activated Carbon					
Z-233	2 (5.1)	3.25 (8.3)		½" FNPT		0.2 (0.1)		5	37	100% Activated Carbon					
Z-234	3.25 (8.3)	3.25 (8.3)		½" FNPT		0.4 (0.2)		5	37	100% Activated Carbon					