



L-Series – In-line, Low Flow Applications

Model	Height inches (cm)	Diameter inches (cm)	Both Ends Connection	Silica Gel lbs (kg)	Carbon Weight lbs (kg)	Maximum Adsorption Capacity fl. ounces (mL)	Maximum Air Flow cfm	Maximum Reservoir Fluid Flow gpm	Type of Medium
L-141	5.5 (14.0)	2 (5.1)	½" FNPT	0.2 (0.1)		1.35 (39)	4	30	100% Silica Gel
L-142	8.5 (21.6)	2 (5.1)	½" FNPT	0.3 (0.1)		2.32 (68)	6	45	100% Silica Gel
L-143	5.5 (14.0)	3.25 (8.3)	½" FNPT	0.8 (0.4)		4.91 (145)	10	75	100% Silica Gel
L-144	8.5 (21.6)	3.25 (8.3)	½" FNPT	1.2 (0.5)		7.87 (232)	10	75	100% Silica Gel
L-241	5.5 (14.0)	2 (5.1)	½" FNPT		0.1 (.05)		6	45	100% Activated Carbon
L-242	8.5 (21.6)	2 (5.1)	½" FNPT		0.2 (0.1)		6	45	100% Activated Carbon
L-243	5.5 (14.0)	3.24 (8.2)	½" FNPT		0.4 (0.2)		6	45	100% Activated Carbon
L-244	8.5 (21.6)	3.24 (8.2)	½" FNPT		0.8 (0.4)		6	45	100% Activated Carbon
L-344	8.5 (21.6)	3.25 (8.3)	½" FNPT	0.9 (0.4)	n/a	4.91 (145)	6	45	33% Activated Carbon 67% Silica Gel